# Tierrafino contact fine product sheet

#### Date: 11/2014

### PRODUCT

| Description:    | Tierrafino Contact Fine is a fine grained primer/mechanical key for clay-<br>paints and stuccos for smooth and/or very absorbing substrates in the interior. |
|-----------------|--|
| Composition:    | Tree resin binder, calcium carbonate, titane oxide, water, additives, preservative.  |
| Packaging:      | 1   and 5   buckets.   |
| Consumption:    | Approx. 0,1 I/m <sup>2</sup> onto smooth substrates. Consumption is greater when applied onto rough substrates.  |
| Storage advice: | Store dry and cool but free of frost.  |
| Workability:    | Once opened, Contact Fine must be used within 1 year.  |

#### AREA OF APPLICATION

| Contact Fine is applied onto smooth and/or very absorbing walls and ceilings in the interior like prepared dry wall systems, smooth gypsum-, |     |
|--|-----|
| lime-, cement- and other plasters, concrete, smooth bricks and other bloc  | ks. |
| Only applicable in the exterior where protected from direct contact with   |     |
| water. Suitable for humid rooms, do not apply where there is a chance of   | f   |
| direct contact with water. Contact Fine is developed to be an adhesion   |     |
| primer for Tierrafino Duro, Listro, I-Paint and T-Paint.   |     |

#### PROPERTIES

- Ready to use
- Easily applied with brush or roller
- White in color before and after drying
- Odorless after drying
- Water vapour permeable
- Not suitable onto humid substrates

#### APPLICATION

| Circumstances: | The air- and substrate temperature must be at least 5°C.   |
|----------------|--|
| Substrate:     | Continuously dry and free of dust and grease. Roughen very smooth, non absorbing surfaces using sandpaper.                                       |
| Mixing:        | Stir well before use.  |
| Application:   | Apply with a brush or a roller. Use a good quality masking tape on substrates and dried out Contact Fine when applying a decorative clay finish. |
| Drying time:   | Under normal circumstances (+20°C and 60% relative air humidity),<br>Contact Fine is dry between 4-12 hours. Hardened out after 2 days.          |
| Thinner:       | Water.   |

## Tierrafino contact fine product sheet

Date: 11/2014

Avoid contact with eyes and mucous membranes. With induced risk (ceilings) wear safety goggles. Keep away from children. For further information consult the Contact Fine Material Safety Data Sheet.



Stirring stick, paint brush, roller, masking tape.



DISCLAIMER

Although this product description has been put together with utmost precision, Tierrafino will not be liable for any indirect or direct damage that may occur, by using the information offered in this product description.